


RF-link Hard of Hearing System

| MODEL | | WARRANTY |
|------------------|---|----------------|
| FHN800HIA | Mains powered with rechargeable battery back-up | 7 YEARS |

- **RF-LINK** Compatible with the FireHawk RF-LINK range of Smoke Alarms (FHB10-RF), Heat Alarms (FHH10-RF), CO Alarms (CO10-RF), RF-Link Module for Mains Alarms (FHN600RF) and the Hard of Hearing Alarm (FHN800HIA)
- **Mains Powered Control Unit with Rechargeable Battery Back up.**
The Control Unit has a high intensity LED Flashing Strobe light to alert the user that an alarm has been activated
- **Vibrating pillow pad**
placed under a pillow will vibrate to alert the user when in bed



Conforms to BS5446-3: 2015



| TECHNICAL SPECIFICATION | |
|----------------------------|--|
| Power Supply | Mains powered with rechargeable battery back-up |
| Alarm Type | Vibrating Pad & Strobe Light |
| Alarm interlink (RF-Link) | Compatible with the FireHawk RF-LINK range of Smoke Alarms (FHB10-RF), Heat Alarms (FHH10-RF), CO Alarms (CO10-RF), RF-Link Module for Mains Alarms (FHN600RF) and the Hard of Hearing Alarm (FHN800HIA) |
| Indicators | GREEN LED (mains power), RED LED (FIRE and CO Alarm) , YELLOW LED (Fault). |
| Device Fixing | Table Stand or Wall Mount. |
| Test/Hush | Test & Silence |
| Dimensions | 75mm x 75mm x 35mm |
| Weight | 0.514 kg |
| Use in: | Dwelling houses, Caravans/motorhomes & Leisure vehicles, Boats. |
| Installation positions | Control unit can be free standing or wall mounted |
| Operating Temperature | -10°C or greater +40°C |
| Operating Humidity | 30% - 90% RH |
| IP Rating | IP42 |
| Packaging | Individual box & Outer carton (Recyclable cardboard) |
| Master pack/Outer carton | 10 units |
| Maximum interlinked alarms | 20 x RF-LINK alarms (Maximum of 15 if used with FHN800HIA) |
| Barcode | EAN - 5055278500900 |
| Approval/Certified to | Conforms to BS5446-3: 2015 |
| Warranty | 7 years |