

Battery RF-link Heat Alarm

MODEL	FHH10-RF	Sealed 10-year lithium battery	WARRANTY	7 YEARS
--------------	-----------------	---------------------------------------	-----------------	----------------

- **RF-LINK** Compatible with the FireHawk RF-LINK range of Smoke Alarms (FHB10-RF), Heat Alarms (FHH10-RF), CO Alarms (CO10-RF), RF-Link Module for Mains Alarms (FHN600RF) and the Hard of Hearing Alarm (FHN800HIA)
- **ADVANCED THERMISTOR** Heat Alarm with bespoke software.
- Small & compact
- Large test/silence button
- Low battery silence - for up to 10 hours
- Ease of linking and installation



TECHNICAL SPECIFICATION	
Supply Voltage	Sealed lithium batteries
Alarm Type	Battery Radio Interlinked Heat Alarm
Alarm interlink (RF-Link)	Compatible with the FireHawk RF-LINK range of Smoke Alarms (FHB10-RF), Heat Alarms (FHH10-RF), CO Alarms (CO10-RF), RF-Link Module for Mains Alarms (FHN600RF) and the Hard of Hearing Alarm (FHN800HIA)
Operating frequency	868MHz
Test/Hush	Large Test/Hush button.
Dimensions	9cm (90mm) diameter x 7.3cm (73mm) Depth
Weight	138g
Alarm Sound level	85dB(A) at 3m
Use in:	Kitchens, garages and lofts
Installation positions	Ceiling or wall
Operating Temperature	0°C – 40°C
Operating Humidity	> 85% RH
Plastic material	ABS Rated at UL94 V-0
Packaging	Individual box & outer carton – recyclable cardboard.
Master pack/Outer carton	10 units
Maximum interlinked alarms	20 x RF-LINK alarms (Maximum of 15 if used with FHN800HIA)
Approval/Certified to	BS 5446-2: 2003
Barcode	EAN 5055278500887
Warranty	7 years